



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]

Features

- Ideal for the robust industrial applications**
- 1 Platform:** IP67, made entirely of stainless steel, silicone-coated stainless load cell. Substraction in wing design, extremely resistant to bending
- 2 Display device:** IP68, very high class of protection against dust and water. Integrated power supply. For further details on the KERN KXS-TM display device, see page 148
- Suitable for the ever-increasing hygienic requirements in the food industry**
- Wall mount standard**
- Superior display size:** digit height 55 mm. Bright backlight for easy reading of weighing results, even in poor lighting conditions

- Thanks to the RS-232, RS-485 and Bluetooth (optional) **interfaces**, the scale can easily be connected to existing networks. Data exchange between the scale, PC or printer
- ESD drain to protect against electrostatic discharge** e.g. for electrostatically-charged weighing objects or people who work with the scale

Technical data


- Large backlit LCD display, digit height 55 mm
- Weighing plate dimensions, stainless steel, WxDxH
 - A 300x240x86 mm, B 400x300x89 mm
 - C 500x400x123 mm, D 650x500x133.5 mm
- Dimensions of display device WxDxH 232x170x80 mm

- Rechargeable battery pack internal**, standard, operating time up to 80 h without backlight, charging time approx. 12 h. Can be re-ordered, KERN GAB-A04
- Cable length of display device approx. 2,5 m


Accessories

- Stand** to elevate display device, must be ordered at purchase, for models with weighing plate size
 - A - D: height of stand approx. 200 mm, KERN IXS-A02
 - B - D: height of stand approx. 400 mm, KERN IXS-A03
 - C - D: height of stand approx. 600 mm, KERN IXS-A04
- Data interface RS-232**, interface cable included approx. 1.5 m, must be ordered at purchase, KERN KXS-A04
- Data interface RS-485**, must be ordered at purchase, KERN KXS-A01
- Bluetooth data interface** for wireless data transfer to PC, must be ordered at purchase, KERN KXS-A02
- Foot switch**, must be ordered at purchase, for details see page 181, KERN KXS-A03
- Suitable printers** see page 177.


STANDARD



OPTION



FACTORY



Model	Weighing range [Max] kg	Readout [d] g	Verification value [e] g	Minimum load [Min] g	Net weight approx. kg	Weighing plate		Options			
								Verification		DAkkS Calibr. Certificate	
								M&I KERN		DKD KERN	
KERN								965-228		963-128	
SXS 6K-3M	3 6	1 2	1 2	20 40	5,1	A		965-228		963-128	
SXS 10K-3M	6 15	2 5	2 5	40 100	5,1	A		965-228		963-128	
SXS 10K-3LM	6 15	2 5	2 5	40 100	11,8	B		965-228		963-128	
SXS 30K-2M	15 30	5 10	5 10	100 200	11,8	B		965-228		963-128	
SXS 30K-2LM	15 30	5 10	5 10	100 200	20,8	C		965-228		963-128	
SXS 60K-2M	30 60	10 20	10 20	200 400	11,8	B		965-229		963-129	
SXS 60K-2LM	30 60	10 20	10 20	200 400	20,8	C		965-229		963-129	
SXS 100K-2M	60 150	20 50	20 50	400 1000	20,8	C		965-229		963-129	
SXS 100K-2LM	60 150	20 50	20 50	400 1000	36,5	D		965-229		963-129	
SXS 300K-2M	150 300	50 100	50 100	1000 2000	36,5	D		965-229		963-129	

Dual-range balance switches automatically to the next largest weighing range [Max] and readout [d].

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

KERN Pictograms:

 Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven).	 Piece counting: Reference quantities selectable. Display can be switched from piece to weight.	 Suspended weighing: Load support with hook on the underside of the balance.
 Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.	 Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total).	 Battery operation: Ready for battery operation. The battery type is specified for each device.
 Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.	 Rechargeable battery pack: Rechargeable set.
 Alibi memory: Electronic archiving of weighing results, complying with the 2009/23/EC standard.	 Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, adjustment of recipe when dosages are exceeded, multiplier function, barcode.	 Universal mains adapter: with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 Data interface RS-232: To connect the balance to a printer, PC or network.		 Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available.
 RS-485 data interface: To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.	 Totalising level A: The weights of similar items can be added together and the total can be printed out.	 Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.
 USB data interface: To connect the balance to a printer, PC or other peripherals.	 Totalising level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, adjustment of recipe when dosages are exceeded, multiplier function, barcode recognition.	 Weighing principle: Strain gauge Electrical resistor on an elastic deforming body.
 Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals.		 Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate.
 WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals.	 Percentage determination: Determining the deviation in % from the target value (100 %).	 Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings.
 Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	 Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision.
 Interface for second balance: For direct connection of a second balance.	 Weighing with tolerance range: Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning.	 Verification possible: The time required for verification is specified in the pictogram.
 Network interface: For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.	 Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value.	 DAkkS calibration possible (DKD): The time required for DAkkS calibration is shown in days in the pictogram.
 Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module.	 Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.	 Package shipment: The time required for internal shipping preparations is shown in days in the pictogram.
 GLP/ISO log: The balance displays the weight, date and time, regardless of a printer connection.	 ATEX explosion protection: Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device.	 Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram.
 GLP/ISO log: With weight, date and time. Only with KERN printers.	 Stainless steel: The balance is protected against corrosion.	 Warranty: The warranty period is shown in the pictogram.

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2000 kg. In combination with a DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe. Thanks to the high level of automation, we can carry out DAkkS calibration of

balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg – 2500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages D, GB, F, I, E, NL, PL